

CHERRY LOG THIN STONE

CHARACTERISTICS

ORIGIN:	USA
GEOLOGY:	Sandstone, Metaquartzite, Quartz
COLOR RANGE:	Brown, Light Gray, Dark Gray, Tan, Red, Pink
FINISH:	Split face
DIMENSIONS:	Piece size varies with average face dimension of 6" to 18" and average thickness of 1" to 3".
WEIGHT:	Thin Stone products are sold by the ton.
COVERAGE:	Approximately 100 -110 square feet per ton as a veneer. Approximately 14-18 cubic feet per ton for stone walls.
FORMATS:	Building Stone, Thin Stone, Irregular Flagstone



USES

House fronts, commercial facades, foundations, columns, chimneys, fireplaces and surrounds, hearths, exterior and interior walls, outdoor kitchens and fireplaces.

FEATURES & BENEFITS

Cherry Log's diverse color palette leaves the finished job rich in color with a "patchwork" effect.

The color range may vary significantly; visual approval of pallets is recommended.

Cherry Log offers a relatively flat face and is an extremely hard, durable material. It will not tool easily, except along natural bedding planes.

The information contained in this document is provided to explain the most commonly asked questions about stone and its uses. This document serves as a general guideline and the information provided within is not meant for exact structural specifications. Frederick Block, Brick & Stone has neither liability, nor can be held responsible, to any person or entity for any misunderstanding, misuses, or misapplication that would cause loss or damage of any kind, including loss of rights, materials, or personal injury, or alleged injury to be caused directly or indirectly by the information contained in this document. Images serve only as a general representation of the material, and approval of the product should be based on the awareness of potential range of color and other characteristics. Please visit one of our showrooms to view a sample of product.